



Ceiling Height Dimensions for Ceiling Hung and Floor to Ceiling Metal Toilet Partitions

Standard Series

Hadrian's Standard series toilet partitions feature 58" (1473mm) high doors and panels mounted 12" (305mm) above the finished floor.

- For Standard ceiling hung installations, the maximum allowable floor to ceiling distance is 123.5" (3137mm).
- For Standard floor to ceiling installations, the maximum allowable floor to ceiling distance is 122" (3099mm).

Elite Series

Featuring 64" (1626mm) high doors and panels mounted 6" (152mm) or 9" (229mm) above the finished floor as well as Hadrian's "No Sightline Solution" to eliminate all sightline gaps, Elite series toilet partitions offer excellent privacy.

- For Elite ceiling hung installations, the maximum allowable floor to ceiling distance is 102" (2591mm).
- For Elite floor to ceiling installations, the maximum allowable floor to ceiling distance is 122" (3099mm).

Elite Plus System

With 72" (1829mm) high doors and 72" (1829mm) high panels mounted 6" (152mm) or 9" (229mm) above the finished floor as well as Hadrian's No Sightline Solution to eliminate all sightline gaps, Elite Plus toilet partitions offer the ultimate in privacy.

- For Elite Plus floor to ceiling installations, the maximum allowable floor to ceiling dimension is 122" (3099mm).
- For Elite Plus ceiling hung installations, the maximum allowable floor to ceiling distance is 102" (2591mm).

Elite Max System

With 73" (1854mm) - 92" (2337mm) high doors and panels mounted 4" (102mm), 6" (152mm) or 9" (229mm) above the finished floor as well as Hadrian's No Sightline Solution to eliminate all sightline gaps, Elite Max toilet partitions offer the ultimate in privacy.

- For Elite Max floor to ceiling installations, the maximum allowable floor to ceiling dimension is 122" (3099mm).

IMPORTANT NOTES:

- Refer to final drawings for wood blocking information as well as Hadrian's "Recommended Methods for Attaching to a Wall". Proper blocking is critical to ensure a rigid installation.
- Structural steel or pre-cast concrete is required as ceiling support. **Wood support is not acceptable.**
- Structural ceiling support and drilling for studs by others. Studs are supplied by Hadrian for installation by others.
- Hadrian supplied ceiling studs **MUST** be used to create a secure installation.

ANSI / ICC requires a 9" (229mm) toe clearance for barrier-free units. As part of their enhanced privacy design, Hadrian's Elite and Elite Plus toilet partitions are mounted 6" (152mm) above the floor. In order to meet the ANSI / ICC toe clearance requirement, the following Elite, Elite Plus and Elite Max styles can be specially manufactured to be mounted 9" (229mm) above the floor upon request:

Elite Headrail Braced, Elite Ceiling Hung, Elite Floor to Ceiling, Elite Plus Floor to Ceiling, Elite Max Floor to Ceiling

Note: Hadrian's Standard series toilet partitions are mounted 12" (305mm) above the floor, which exceeds the ANSI / ICC toe clearance requirement for barrier-free units.

ALWAYS ENSURE THAT YOU ADHERE TO APPLICABLE CODE REQUIREMENTS IN YOUR AREA.